Odorox[®] Slimline[™] Air & Surface Purifiers



The Odorox Slimline family of purifiers delivers effective air and surface treatment of odors, smoke, mold, and pathogens for various spaces, from light commercial to restoration and remediation environements. The Whisper models offer ultra-quiet operation for noise-sensitive environments like offices, schools, and senior living. The MAX models provide increased treatment power for enhanced sanitization and deodorization in demanding industrial settings.

	Odorox Slimline™ Purifier	Odorox Slimline MAX™ Industrial Purifier	Odorox Slimline Whisper™ Purifier	Odorox Slimline Whisper MAX™ Industrial Purifier
TREATMENT RANGE	UP TO 900 ft ^{2*} (84 m ²)	UP TO 1,500 ft ^{2*} (139 m ²)	UP TO 900 ft ^{2*} (84 m ²)	UP TO 1,500 ft ^{2*} (139 m ²)
NOISE LEVEL (at low speed)	58 dB	58 dB	46 dB	46 dB
DIMENSIONS (LxWxD)	25" x 18" x 5.2" (635 mm x 457 mm x 133 mm)			
WEIGHT	17.6 lbs (7.9 kg)			
VOLTAGE	120V @ 60Hz /OR/ 230V @ 50Hz			
POWER	170 Watts (Max)			
NUMBER OF OPTICS	1			
FILTER	Washable filter 5.0" x 12.5" x 0.25" (127mm x 317mm x 6mm)			
SHIPPING DIMENSIONS	21" x 9" x 29" (533mm x 229mm x 737mm)			
SHIPPING WEIGHT	21.6 lbs (9.8 kg)			
CERTIFICATION	UL 507, CSA C22.2 #113, CE, RoHs, REACH			
WARRANTY	2 years covering defects in workmanship or materials, but excluding consumables			
PRODUCT NUMBERS				
120V MODEL	00819355020294	00819355021161	00819355021673	00819355021109
230V MODEL	00819355022151	00819355020683	00819355021017	00819355021024
REPLACEMENT OPTIC	00819355021154	00819355021130	00819355021154	00819355021130

*Based on typical operating conditions: 3 air changes per hour, 90% recirculated air, and 9-foot (2.7 m) ceiling. The Slimline™ MAX guidelines will be reduced with higher contamination levels. Contact Pyure for modifications to these guidelines.

